


RI-10S10C-2B2048-H1181

Incremental Encoder

Industrial Line



Features


- Clamping flange, Ø 58 mm
- Solid shaft, Ø 10 mm × 20 mm
- Optical measuring principle
- Shaft material: stainless steel
- Protection class IP67 on housing and shaft side
- -40...+85 °C
- Max. 6000 rpm (continuous operation 3000 rpm)
- 10...30 VDC
- Push-pull/HTL with inversion
- Pulse frequency max. 300 kHz
- M12 × 1 male, 8-pin
- 2048 pulses per revolution

Technical data

Type	RI-10S10C-2B2048-H1181
Ident. no.	1545205
Measuring principle	Photoelectric
Max. Rotational Speed	6000 rpm
Moment of inertia of the rotor	1.8 x 10 ⁻⁶ kgm ²
Starting torque	< 0.05 Nm
Ambient temperature	-40...+85 °C
Operating voltage	10...30 VDC
No-load current	≤ 100 mA
Output current	≤ 30 mA
Short-circuit protection	yes
Wire breakage/Reverse polarity protection	yes
Output function	Push-Pull/HTL, invertable
Output type	incremental
Resolution, incremental	2048 ppr
Pulse frequency max.	300 kHz
Signal level high	min. U _B - 1 V
Signal level low	max. 0.5 V
Design	Solid shaft
Flange type	Clamping flange
Flange diameter	Ø 58 mm
Shaft Type	Solid shaft
Shaft diameter D (mm)	10
Shaft length X	20 mm
Shaft material	Stainless steel
Housing material	Die-cast zinc

Wiring diagram

1	GND
2	U _B +
3	A
4	A inv.
5	B
6	B inv.
7	0 -
8	0 inv. -
PH	shield




Technical data

Electrical connection	Connectors, M12 × 1
	8-pin
Axial shaft load	50 N
Radial shaft load	100 N
Vibration resistance (EN 60068-2-6)	300 m/s ² , 10...2000 Hz
Shock resistance (EN 60068-2-27)	3000 m/s ² 6 ms
Protection class housing	IP67
Protection class shaft	IP67

Signal	Gnd	+U _s	A	A inv.	B	B inv.	0	0 inv.	Shield
Pin configuration	1	2	3	4	5	6	7	8	PH


Accessories

RCS-19-10-10

1545356



Bellows coupling, outer diameter:
19 mm, bore diameter: 10 mm/10 mm

RCS-19-10-08

1545357



Bellows coupling, outer diameter:
19 mm, bore diameter: 10 mm/8 mm

RCS-19-10-06

1545358



Bellows coupling, outer diameter:
19 mm, bore diameter: 10 mm/6 mm

RCS-19-12-10

1545355



Bellows coupling, outer diameter:
19 mm, bore diameter: 12 mm/10 mm

RFA-2

1544631



Aluminium flange adapter, rectangular,
for solid shaft encoders with clamping
flange; edge length 63.5 mm; 3 mm
thick

RFA-13

1544642



Aluminium flange adapter, rectangular,
for solid shaft encoders with clamping
flange; edge length 80 mm; 4 mm thick

RFA-1

1544630



Aluminium flange adapter, rectangular,
for solid shaft encoders with clamping
flange; edge length 58 mm; 4 mm thick

RFA-4

1544633



Euro flange – aluminium flange adapter
for solid shaft encoders, Ø 115 mm;
reference diameter 100 mm; adapts 58
mm clamping flange to Euro flange

RFA-6

1544635


Aluminium flange adapter for solid shaft
encoders with clamping flange, Ø 58
mm; adapts clamping flange to synchro
flange


RFA-7

1544636


Aluminium flange adapter for solid shaft
encoders, Ø 65 mm; adapts to Ø 65 mm
flange and 48 mm reference diameter

RFA-8


1544637



Aluminium flange adapter for solid shaft encoders with clamping flange, Ø 70 mm; thickness 4 mm, adapts to Ø 70 mm flange

RFA-9


1544638



Aluminium angle flange for solid shaft encoders with Ø 58 mm clamping flange

RFA-11


1544640



Aluminium flange adapter for solid shaft encoders with clamping flange, Ø 70 mm; thickness 10 mm, adapts to Ø 70 mm flange

RFA-12

1544641



Aluminium flange adapter, rectangular, for solid shaft encoders with clamping flange; edge length 70 mm; 10 mm thick